

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

1 Identification

- **Product identifier**
- **Trade name:** **GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER**
- **Article number:** 227934 - 200ml / 227935 - 25ml
- **Application of the substance / the mixture** Hair Cosmetics
- **Manufacturer/Supplier:**
Kao USA Inc.
2535 Spring Grove Avenue
Cincinnati, Ohio 45214 / USA
KaoGermanySDS@kao.com
- **Information department:** CHEMTREC
- **Emergency telephone number:**
CHEMTREC (US): (0800) 424-9300
CHEMTREC (Outside US): +1 (703) 527-3887 (24h)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapor.

- **Label elements**
- **Hazard pictograms**



GHS02

- **Signal word** Warning
- **Hazard statements**
H226 Flammable liquid and vapor.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 1)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5	ethanol ⚠ Flam. Liq. 2, H225	2.5-<10%
CAS: 4065-45-6	Benzophenone-4 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	0.2-0.7%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:** Treat symptomatically.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

CAS: 64-17-5 ethanol (2.5-<10%)

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Not required under normal conditions. The details concerned are recommendations.

The glove material has to be impermeable and resistant to the product / the substance / the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. - Please contact the glove supplier for further information.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 3)

· Eye protection:


Not required under normal conditions
If there is a risk of splashing: safety glasses

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value at 20 °C (68 °F):** 4.5

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· **Flash point:** 55 °C (131 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17 mm Hg)

· **Density at 20 °C (68 °F):** 1.0049 g/cm³ (8.386 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	0 s (DIN 53211/4)

· Solvent content:

Organic solvents:	6.0 %
Water:	86.4 %
VOC content:	6.0 %

Solids content: 7.3 %

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No dangerous reactions known if used as directed.
- **Chemical stability** The product is stable under standard conditions.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 4)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 64-17-5	ethanol	1
CAS: 97-53-0	Eugenol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, IMDG, IATA** UN1993

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 5)

· **UN proper shipping name**
 · **DOT** *Flammable liquids, n.o.s. (Ethanol)*
 · **IMDG, IATA** *FLAMMABLE LIQUID, N.O.S. (ETHANOL)*

· **Transport hazard class(es)**
 · **DOT**



· **Class** *3 Flammable liquids*
 · **Label** *3*

· **ADR/RID/ADN, IMDG, IATA**



· **Class** *3 Flammable liquids*
 · **Label** *3*

· **Packing group**
 · **DOT, ADR/RID/ADN, IMDG, IATA** *III*

· **Environmental hazards:** *Not applicable.*

· **Special precautions for user** *Warning: Flammable liquids*
 · **Danger code (Kemler):** *30*
 · **EMS Number:** *F-E, S-E*
 · **Stowage Category** *A*

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** *On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L*

· **IMDG**
 · **Limited quantities (LQ)** *5L*
 · **Excepted quantities (EQ)** *Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml*

· **UN "Model Regulation":** *UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHANOL), 3, III*

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 122-99-6 | 2-Phenoxyethanol

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: GOLDWELL STYLESIGN ULTRA VOLUME SOFT VOLUMIZER

(Contd. of page 6)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 | ethanol

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 64-17-5 | ethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

· Department issuing SDS: Regulatory Affairs
· Date of preparation / last revision 04/04/2017 / 2
· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1B: Skin sensitisation – Category 1B

· * Data compared to the previous version altered.